FUJIFILM
I&I – Imaging & Information

2.0M Effective Pixels

ZOOM 3X Optical 2.5X Digital

DIGITAL CAMERA

FinePix A205

New

Beautiful digital photography at its simplest and easiest

- ***2.0 million effective pixels*** *for high-quality images*
- ***3X optical + 2.5X digital zoom***
- *Multi-language LCD display*
- *Low power consumption using two standard AA batteries*
- *Movie recording function*
- *Optional PictureCradle for easy link to any PC*

digital
Tools for the imagination.

AF

MOVIE REC

xD-Picture Card™

FinePix

The FinePix A205: Turn the good times into great photographic memories

Outstanding image quality

With 2.0 million effective pixels, the FinePix A205 delivers high-resolution images with crisp details and brilliant colors – perfect for making high-quality photo prints. There's no easier way to make sure you're always ready to capture all the fun and excitement in beautiful digital images.

High-performance zooming

The FinePix A205 sports a high-performance Fujinon 3✕ optical zoom lens (equivalent to 36-108mm on a 35mm camera), making it easy to frame your subject perfectly. A smooth digital zoom function offers up to 2.5✕* additional magnification.

** At 640 × 480-pixel mode*

One-touch, fully automatic operation

Your new camera comes complete with batteries and a 16MB xD-Picture Card™, so you can start taking pictures right away. Then just press the shutter button – and welcome to the world of digital photography. The FinePix A205 automatically controls focus, exposure, and white balance to give you great photos, first time and every time.

Low-power consumption

Thanks to its power-saving design, the FinePix A205 lets you take up to 300 shots* on a single pair of AA batteries.

** With the LCD turned off and using the flash for 50% of shots*

Multi-language LCD display

All menus can be displayed in any of six languages: English, French, German, Spanish, Chinese, or Japanese. The easy-to-use LCD menus make it a breeze to change settings to your own personal preferences.

xD-Picture Card™ support

The FinePix A205 is designed around the ultra-compact xD-Picture Card™*. This versatile new memory card standard offers a number of advantages, including effortless PC data transfer with any compatible USB card reader or PC/CompactFlash™ card adapter.

** Supports card capacities of up to 512MB.*

Optional PictureCradle

The PictureCradle, available separately, provides a simple and stylish way to automatically upload image files to your PC while simultaneously recharging the camera battery. Dedicated AC adapter and rechargeable battery are included with the PictureCradle.

With optional PictureCradle

Other features

- Movie recording function*
- Video output to a TV monitor
- Macro focus to 10cm

** Up to 20 seconds at 320 × 240 pixels*

Specifications

DIGITAL CAMERA FinePix A205

Number of effective pixels*	2.0 million pixels
CCD sensor	1/2.7-inch CCD (Number of total pixels: 2.11 million pixels)
Number of recorded pixels	Still image: 1600 × 1200 (1.9 million)/1280 × 960/640 × 480 pixels Movie: 320 × 240 pixels (10 frames/sec., without sound), 160 × 120 pixels (10 frames/sec., without sound)
Storage media	xD-Picture Card™ (16MB to 512MB)
File format	Still image: JPEG (Exif Ver. 2.2**)/Movie: AVI (Motion JPEG) [Design rule for Camera File system compliant/DPOF-compatible]

Number of images/recording time

Modes	Still image			Movie	
Image quality mode displayed	2M	1M	0.3M	320	160
Number of recorded pixels	1600 × 1200	1280 × 960	640 × 480	320 × 240 (10 fps)	160 × 120 (10 fps)
DPC-16 (16MB)	25	33	122	Approx. 98 sec.	Approx. 5.6 min.
DPC-32 (32MB)	50	68	247	Approx. 199 sec.	Approx. 11.3 min.
DPC-64 (64MB)	101	137	497	Approx. 6.6 min.	Approx. 22.7 min.
DPC-128 (128MB)	204	275	997	Approx. 13.3 min.	Approx. 45.5 min.
DPC-256 (256MB)	409	550	1,997	Approx. 26.7 min.	Approx. 91.2 min.
DPC-512 (512MB)	818	1,101	3,993	Approx. 53.5 min.	Approx. 182.5 min.

The numbers of images and recording time will vary slightly depending on the type of subject.

Lens	Fujinon 3✕ optical zoom lens, F3.0 – F4.8
Lens focal length	Equivalent to 36 – 108mm on a 35mm camera
Focus	Autofocus
Focus distance	Normal: Approx. 80 cm/2.6 ft. to infinity Macro: Approx. 10 cm – 1.0 m/0.3 ft – 3.3 ft
Aperture	F3.0/F7.0 (wide-angle) – F4.8/F10.8 (telephoto)
Sensitivity	Equivalent to ISO 100 (at flash off)
LCD monitor	1.5-inch D-TFD (55,000 pixels)
Flash	Automatic, 3.5m/11.5ft (max.)
Terminal	Multiple connecter (for USB 1.1 or optional PictureCradle), Video output socket
Video output	NTSC/PAL selectable
Power source	2 AA Alkaline/Ni-MH battery or AC power adapter (optional)
Dimensions	98.5 (W) × 65.0 (H) × 52.5 (D) mm/3.9 (W) × 2.6 (H) × 2.1 (D) in.
Weight	175g/6.2oz. (excluding batteries and media)

Camera functions	
Digital zoom	2.5✕ (640 × 480 pixels), 1.25✕ (1280 × 960 pixels)
Shooting modes	Auto, Manual
Movie recording	320 × 240 pixels: 10 frames/sec., up to 20 sec. 160 × 120 pixels: 10 frames/sec., up to 80 sec. without sound, AVI format (Motion JPEG)
Playback	Single frame (with 10✕ Playback zoom at 2M mode), 9 Multi-frame
Accessories included	16 MB xD-Picture Card™ 2 AA type alkaline batteries Hand strap USB cable Video cable Cradle adapter for FinePix A205 CD-ROM: USB driver, FinePixViewer, ImageMixer VCD for FinePix
Optional accessories	xD-Picture Card™: DPC-16, DPC-32, DPC-64, DPC-128, DPC-256, DPC-512 AC Power Adapter AC-3V (Cannot be used as a battery charger for this model) PictureCradle CP-FXA10 (Includes AC-3VW and Rechargeable Battery NH-10, which can be charged only in this cradle) Battery Pack NH-10 (Can be charged with PictureCradle CP-FXA10) PC Card Adapter DPC-AD Image Memory Card Reader DPC-R1 CompactFlash™ Card Adapter DPC-CF Battery Charger with Battery BK-NH2/BK-NH Rechargeable Battery 2HR-3UF (2 Ni-MH batteries included) Soft Case SC-FX26

* Number of effective pixels: The number of pixels on the image sensor which receive input light through the optical lens, and which are effectively reflected in the final output data of the still image.

** Exif 2.2 is a newly revised digital camera file format that contains a variety of shooting information for optimal printing.

Exif Print

Windows® XP compatible

Specifications are subject to change without notice.

xD-Picture Card™ and all other trademarks are the property of their respective holders.

For more information on the full range of Fujifilm digital products, please visit our Website: ***http://home.fujifilm.com***

FUJIFILM
FUJI PHOTO FILM CO., LTD.
26-30, NISHIAZABU 2-CHOME, MINATO-KU, TOKYO 106-8620, JAPAN

Ref. No. EB-308E (SK·03·06·DT·MW) Printed in Japan © 2003 Fuji Photo Film Co., Ltd.